

FEATURES

- Super-Symmetric (2 in 1) arms increase overall arm sweep and minimum arm reach to precisely lift vehicles
- Dual hydraulic direct-drive cylinders
- Single-point safety release allow technician to disengage both column simultaneously
- Self-lubricating UHMW Polyethylene sliders and bronze bushings
- Clear-floor design, provides unobstructed floor use
- Overhead safety shut-off device prevents vehicle damage
- Stackable adapters 1.5", 3", 6" are standard
- 4 Frame Adapters Included
- Standard adjustable heights accommodates varying ceiling heights
- Standard door guards and toe guards on lifting arms
- Automatic swing arm restraints
- Anchor Bolts Included

PRODUCT SPECS

- Lifting Capacity: 9000 LB.
- Drive Thru: 97 1/2" (8' 1 1/2")
- Motor Rating: 3HP, 220V, 1 PH, 30A
- Overall Floor Width: 135" (11' 3")
- Overall Height 142 1/2" (11' 10 1/2") or 150 1/2" (12' 6 1/2")
- Lifting Height: 71" – 81" (5' 11") to (6' 9")
- Low Pad Height: 4 1/4"
- Width Between Columns: 112 1/4" (9' 4 1/4")
- Shipping Weight: 1450LB.
- Concrete Requirement: 4" Depth, 3000 PSI Rebar Reinforced
- Base Plate: 15 5/8" X 17 5/8" (1' 3 5/8" x 1' 5 5/8")
- Lifting Time: 50 Seconds